



SOLENOID VALVE G44230

The Solenoid Valve G44230 is a two-stage valve, intended for Natural or Bio gas operated heavy vehicles (trucks or busses). The Valve is delivered complete with stainless steel tube fittings for mm or inch tubes. To provide long-term high performance in harsh conditions, the solenoid valve is protected by an electronic system (Electronic Unit P/N: G83410BADAB).

The Valve is approved according to the United Nations Economic Commission for Europe Regulation No. 110 (ECE-R110) for CNG Vehicles, approval No. 000130.



P/N: G44230



P/N: G83410BADAB



P/N: G84268/_m

Technical Data:

- Corresponding valves are available for alternative gases and other pressure rates.
- Voltage: 12 or 24V DC.
- Max working pressure: 260 bar.
- Temperature range: -40°C to 105°C (-40°F to 221°F).
- Weight: ~0,7 kg incl. fittings (Electronic Unit ~0,5 kg)

E1 110 R - 000130



All above specifications are standard and subject to change without notice

8BR026GB 0905:2



Postadress/Postal address

GAVECO AB
Box 2103
SE-135 02 TYRESÖ

Besöksadress/Visiting address

Vendelsövägen 21
Trollbäcken-Stockholm

Tel +46(0)8-742 00 00
Fax +46(0)8-798 88 81
www.gaveco.se